

Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. A

Revision date: 13.12.2022

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ATA 2004C, Comp. A

UFI: 5J4W-10K2-H008-J9AF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesive mortar for fastening elements A-component (resin)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: TOGE Dübel GmbH & Co. KG

Street: Illesheimer Straße 10

Place: D-90431 Nürnberg

Telephone: +49 (0)911-65968-0

e-mail: info@toge.de

Internet: www.toge.de

1.4. Emergency telephone number:

+49 (0)551-19240 (GIZ-Nord, German and English 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Irrit. 2; H315

Eye Irrit. 2; H319

Skin Sens. 1; H317

Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling


2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane;

Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol;

1,6-Bis(2,3-epoxypropoxy)hexane

Signal word: Warning

Pictograms:



Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P264 Wash hands thoroughly after handling.

P273 Avoid release to the environment.



Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. A

Revision date: 13.12.2022

Page 2 of 13

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P391 Collect spillage.

Special labelling of certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

People who are allergic to epoxide should avoid the use of the product.
Use only outdoors or in a well-ventilated area.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
1675-54-3	2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane			25 - < 50 %
	216-823-5	603-073-00-2	01-2119456619-26	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
-	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol			10 - < 20 %
	701-263-0		01-2119454392-40	
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411			
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane			10 - < 20 %
	618-939-5		01-2119463471-41	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H319 H317 H412			
	Alkyl Ester (Ref.: 722 43/00/2012.0028, Germany)			1 - 10 %
	Eye Irrit. 2; H319			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
1675-54-3	216-823-5	2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	25 - < 50 %	
	dermal: LD50 = 23000 mg/kg; oral: LD50 = 15000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100			
-	701-263-0	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	10 - < 20 %	
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg			
933999-84-9	618-939-5	1,6-Bis(2,3-epoxypropoxy)hexane	10 - < 20 %	
	inhalation: LC50 = 0,035 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 2190 mg/kg			
	Alkyl Ester (Ref.: 722 43/00/2012.0028, Germany)			1 - 10 %
	dermal: LD50 = 2000 mg/kg; oral: LD50 = 20700 mg/kg			

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.



Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. A

Revision date: 13.12.2022

Page 3 of 13

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam

Extinguishing powder

Water spray jet

Carbon dioxide (CO₂)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic

Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.



Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. A

Revision date: 13.12.2022

Page 4 of 13

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.

Wash hands thoroughly after handling. When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Store in a place accessible by authorized persons only.

Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Oxidising agent, strong

Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

storage temperature: 5 - 35°C

7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

**Safety Data Sheet**

according to UK REACH Regulation

ATA 2004C, Comp. A

Revision date: 13.12.2022

Page 5 of 13

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
-	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol			
Worker DNEL, acute		dermal	local	0,0083 mg/cm ²
Worker DNEL, long-term		dermal	systemic	104,15 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	29,39 mg/m ³
Consumer DNEL, long-term		dermal	systemic	62,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	8,7 mg/m ³
Consumer DNEL, long-term		oral	systemic	6,25 mg/kg bw/day
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane			
Worker DNEL, long-term		inhalation	systemic	10,57 mg/m ³
Worker DNEL, long-term		inhalation	local	0,44 mg/m ³
Worker DNEL, long-term		dermal	systemic	6,0 mg/kg bw/day
Worker DNEL, long-term		dermal	local	0,0226 mg/cm ²
Consumer DNEL, long-term		inhalation	systemic	5,29 mg/m ³
Consumer DNEL, long-term		inhalation	local	0,27 mg/m ³
Consumer DNEL, long-term		dermal	systemic	3,0 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,0136 mg/cm ²
Consumer DNEL, acute		inhalation	systemic	5,29 mg/m ³
Consumer DNEL, acute		dermal	systemic	1,7 mg/kg bw/day
Consumer DNEL, acute		dermal	local	0,0136 mg/cm ²
Consumer DNEL, long-term		oral	systemic	1,5 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	1,5 mg/kg bw/day

PNEC values

CAS No	Substance	Value
-	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	
Freshwater		0,003 mg/l
Marine water		0,0003 mg/l
Freshwater sediment		0,294 mg/kg
Marine sediment		0,0294 mg/kg
Secondary poisoning		0,0254 mg/l
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,237 mg/kg
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane	
Freshwater		0,0115 mg/l
Marine water		0,00115 mg/l
Freshwater sediment		0,283 mg/kg
Marine sediment		0,283 mg/kg

Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. A

Revision date: 13.12.2022

Page 6 of 13

Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. Wear safety glasses.

Hand protection

Recommended material: NBR (Nitrile rubber)
Breakthrough time: > 480 min
Thickness of the glove material: 0,7 mm
DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	solid (pasty)
Colour:	light beige
Odour:	characteristic
Odour threshold:	No data available

Changes in the physical state

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flash point:	not applicable

Flammability

Solid/liquid:	not determined
Gas:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined

Self-ignition temperature

Solid:	not determined
--------	----------------



Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. A

Revision date: 13.12.2022

Page 7 of 13

Gas:	not applicable
Decomposition temperature:	not determined
pH-Value:	not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure: not determined

Density (at 20 °C): 1,49 g/cm³

Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties
Not oxidising.

Other safety characteristics

Solid content: not determined

Evaporation rate: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent, strong

10.4. Conditions to avoid

Heat. Keep cool. Protect from sunlight.

10.5. Incompatible materials

Keep away from: Oxidizing agent

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

**Safety Data Sheet**

according to UK REACH Regulation

ATA 2004C, Comp. A

Revision date: 13.12.2022

Page 8 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1675-54-3	2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane				
	oral	LD50 15000 mg/kg	Rat		
	dermal	LD50 23000 mg/kg	Rabbit		
-	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane				
	oral	LD50 2190 mg/kg	Rat		OECD 401
	dermal	LD50 > 2000 mg/kg	Rat		OECD 402
	inhalation (4 h) vapour	LC50 0,035 mg/l	Rat		
	Alkyl Ester (Ref.: 722 43/00/2012.0028, Germany)				
	oral	LD50 20700 mg/kg	Mouse		
	dermal	LD50 2000 mg/kg	Rabbit		

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Contains epoxy constituents. May produce an allergic reaction. May cause an allergic skin reaction. (2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol; 1,6-Bis(2,3-epoxypropoxy)hexane)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. A

Revision date: 13.12.2022

Page 9 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1675-54-3	2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane					
	Acute fish toxicity	LC50	2 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	11 mg/l	72 h		
	Acute crustacea toxicity	EC50	1.8 mg/l	48 h	Daphnia magna (Big water flea)	
-	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol					
	Acute fish toxicity	LC50	2,54 mg/l	96 h	Danio rerio (zebrafish)	
	Acute algae toxicity	ErC50	1,8 mg/l	96 h	Selenastrum capricornutum	
	Acute crustacea toxicity	EC50	2,55 mg/l	48 h	Daphnia magna (Big water flea)	
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane					
	Acute fish toxicity	LC50	30 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute crustacea toxicity	EC50	47 mg/l	48 h	Daphnia magna (Big water flea)	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
-	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol				
	OECD 301B	16 %	28		
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane				
	OECD 301D	71 %	28		

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
-	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	3,3
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane	0,822

BCF

CAS No	Chemical name	BCF	Species	Source
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane	3,57		

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. A

Revision date: 13.12.2022

Page 10 of 13

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 3077
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epoxy resin)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9



Classification code:	M7
Special Provisions:	274 335 375 601
Limited quantity:	5 kg
Excepted quantity:	E1
Transport category:	3
Hazard No:	90
Tunnel restriction code:	-

Other applicable information (land transport)

No dangerous goods in packaging until 5 kg according special instruction 375 ADR/RID

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 3077
--------------------------------------	---------

Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. A

Revision date: 13.12.2022

Page 11 of 13

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
 (Epoxy resin)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9



Classification code: M7
 Special Provisions: 274 335 375 601
 Limited quantity: 5 kg
 Excepted quantity: E1

Other applicable information (inland waterways transport)

No dangerous goods in packaging until 5kg according special instruction 375 ADN

Marine transport (IMDG)

14.1. UN number or ID number: UN 3077
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
 (Epoxy resin)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9



Special Provisions: 274, 335, 966, 967, 969
 Limited quantity: 5 kg
 Excepted quantity: E1
 EmS: F-A, S-F

Other applicable information (marine transport)

No dangerous goods in packaging until 5kg according 2.10.2.7 IMDG-Code

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3077
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
 (Epoxy resin)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9



Special Provisions: A97 A158 A179 A197
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y956
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 956
 IATA-max. quantity - Passenger: 400 kg
 IATA-packing instructions - Cargo: 956
 IATA-max. quantity - Cargo: 400 kg

Other applicable information (air transport)

No dangerous goods in packaging until 5kg according A197 IATA-DGA

14.5. Environmental hazards

Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. A

Revision date: 13.12.2022

Page 12 of 13

ENVIRONMENTALLY HAZARDOUS: Yes



14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to 2012/18/EU E2 Hazardous to the Aquatic Environment (SEVESO III):

Additional information

VOC content: 0,9 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADN: Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level

DNEL: Derived No Effect Level

EC50: Effective concentration, 50%

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

IMDG: International Maritime Dangerous Goods Code

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Organisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic

vPvB: very persistent and very bioaccumulative

PNEC: Predicted No Effect Concentration

**Safety Data Sheet**

according to UK REACH Regulation

ATA 2004C, Comp. A

Revision date: 13.12.2022

Page 13 of 13

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Aquatic Chronic 2: Long-term aquatic hazard, Category 2

Aquatic Chronic 3: Long-term aquatic hazard, Category 3

Eye Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Sens. 1: Skin sensitization, Category 1

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. B

Revision date: 13.12.2022

Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ATA 2004C, Comp. B

UFI: GN4W-J08F-T00R-6MWH

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

compound mortar B-component (hardener)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: TOGE Dübel GmbH & Co. KG
Street: Illesheimer Straße 10
Place: D-90431 Nürnberg
Telephone: +49 (0)911-65968-0
e-mail: info@toge.de
Internet: www.toge.de

1.4. Emergency telephone number:

+49 (0)551-19240 (GIZ-Nord, German and English 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Acute Tox. 4; H302
Skin Corr. 1B; H314
Eye Dam. 1; H318
Skin Sens. 1; H317
Muta. 2; H341
Repr. 1A; H360F
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

3-aminomethyl-3,5,5-trimethylcyclohexylamine;
Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine);
m-Phenylenebis(methylamine);
Formaldehyde, oligomeric reaction products with 4,4'-isopropylidenediphenol and diethylenetriamine;
2,4,6-Tris(dimethylaminomethyl)phenol;
Diethylenetriamine;
Phenol;
Bisphenol A

Signal word: Danger**Pictograms:**



Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. B

Revision date: 13.12.2022

Page 2 of 17

Hazard statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.
H360F	May damage fertility.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P201	Obtain special instructions before use.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P310	Immediately call a POISON CENTER/doctor.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

Contains Amines. May produce an allergic reaction.
Use only outdoors or in a well-ventilated area.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

**Safety Data Sheet**

according to UK REACH Regulation

ATA 2004C, Comp. B

Revision date: 13.12.2022

Page 3 of 17

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine			30 - < 40 %
	220-666-8	612-067-00-9	01-2119514687-32	
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A; H302 H314 H318 H317			
1950616-36-0	Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine)			15 - < 25 %
	701-207-5		01-2119966906-20	
	Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1B, Aquatic Chronic 3; H314 H318 H317 H412			
1477-55-0	m-Phenylenebis(methylamine)			15 - < 25 %
	216-032-5		01-2119480150-50	
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1B, Aquatic Chronic 3; H332 H302 H314 H318 H317 H412			
77138-45-5	Formaldehyde, oligomeric reaction products with 4,4'-isopropylidenediphenol and diethylenetriamine			< 10,5 %
	500-263-6		01-2120769506-44	
	Repr. 2, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, STOT SE 3; H361 H314 H318 H317 H335			
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol			5 - < 10 %
	202-013-9		01-2119560597-27	
	Acute Tox. 4, Skin Corr. 1C, Eye Dam. 1; H302 H314 H318			
100-51-6	Benzyl alcohol			5 - < 10 %
	202-859-9	603-057-00-5	01-2119492630-38	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2; H332 H302 H319			
111-40-0	Diethylenetriamine			< 7 %
	203-865-4	612-058-00-X	01-2119473793-27	
	Acute Tox. 2, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, STOT SE 3; H330 H312 H302 H314 H318 H317 H335			
108-95-2	Phenol			1 - < 5 %
	203-632-7	604-001-00-2	01-2119471329-32	
	Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Eye Dam. 1, STOT RE 2, Aquatic Chronic 2; H341 H331 H311 H301 H314 H318 H373 H411			
71074-89-0	Bis[(dimethylamino)methyl]phenol			1 - < 5 %
	275-162-0			
	Skin Corr. 1B, Eye Dam. 1; H314 H318			
80-05-7	Bisphenol A			< 2 %
	201-245-8	604-030-00-0	01-2119457856-23	
	Repr. 1B, Eye Dam. 1, Skin Sens. 1, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1; H360F H318 H317 H335 H400 H410			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. B

Revision date: 13.12.2022

Page 4 of 17

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
2855-13-2	220-666-8	3-aminomethyl-3,5,5-trimethylcyclohexylamine oral: ATE 1030 mg/kg Skin Sens. 1A; H317: >= 0,001 - 100	30 - < 40 %
1477-55-0	216-032-5	m-Phenylenebis(methylamine) inhalation: LC50 = 3,89 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 2000 mg/kg; oral: LD50 = 930 mg/kg	15 - < 25 %
90-72-2	202-013-9	2,4,6-Tris(dimethylaminomethyl)phenol dermal: LD50 = 1280 mg/kg; oral: LD50 = 2169 mg/kg	5 - < 10 %
100-51-6	202-859-9	Benzyl alcohol inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = 1230 mg/kg	5 - < 10 %
111-40-0	203-865-4	Diethylenetriamine inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = 1054 mg/kg; oral: LD50 = 1080 mg/kg	< 7 %
108-95-2	203-632-7	Phenol inhalation: ATE = 3 mg/l (vapours); inhalation: LC50 = 0,9 mg/l (dusts or mists); dermal: LD50 = 630 mg/kg; oral: LD50 = 650 mg/kg Skin Corr. 1B; H314: >= 3 - 100 Skin Irrit. 2; H315: >= 1 - < 3 Eye Irrit. 2; H319: >= 1 - < 3	1 - < 5 %
80-05-7	201-245-8	Bisphenol A dermal: LD50 = 3000 mg/kg; oral: LD50 = 3250 mg/kg M acute; H400: M=1 M chron.; H410: M=10	< 2 %

Further Information

SVHC list (Candidate List of Substances of Very High Concern for authorization): The product contains one of the listed substances: Bisphenol A

This mixture is placed on the market in a form in which aerosol formation cannot occur during intended use and may only be used for applications in which aerosol formation is excluded. Workplace measurements to determine the exposure of users towards contained hazardous substances were carried out. Test reports show no need for the classification of the product as toxic by inhalation. The test reports are available. According to Article 6 of Regulation EC No. 1272/2008, classification and labeling as inhalation toxic is therefore not required.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.



Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. B

Revision date: 13.12.2022

Page 5 of 17

4.2. Most important symptoms and effects, both acute and delayed

Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Suspected of causing genetic defects.
May damage fertility.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam
Extinguishing powder
Water spray jet
Carbon dioxide (CO₂)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic
Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.
Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand
Treat the recovered material as prescribed in the section on waste disposal.
Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling



Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. B

Revision date: 13.12.2022

Page 6 of 17

Advice on safe handling

- Use only outdoors or in a well-ventilated area.
- Wear personal protection equipment (refer to section 8).
- Avoid contact with skin, eyes and clothes.
- When using do not eat, drink or smoke.

Advice on general occupational hygiene

- Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.
- Wash hands thoroughly after handling. When using do not eat, drink or smoke. Avoid contact during pregnancy and while nursing.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep container tightly closed.
- Store in a place accessible by authorized persons only.
- Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

- Do not store together with: Oxidising agent, strong, Organic peroxides
- Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

- Keep container tightly closed in a cool place.
- storage temperature: 5 - 35°C

7.3. Specific end use(s)

see section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
111-40-0	2,2'-Iminodi(ethylamine)	1	4.3		TWA (8 h)	WEL
80-05-7	Bisphenol A, inhalable dust	-	2		TWA (8 h)	WEL
108-95-2	Phenol	2	7.8		TWA (8 h)	WEL
		4	16		STEL (15 min)	WEL

Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. B

Revision date: 13.12.2022

Page 7 of 17

DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
1950616-36-0	Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine)		
Worker DNEL, long-term	inhalation	systemic	0,02 mg/m ³
Worker DNEL, acute	inhalation	systemic	2,0 mg/m ³
Worker DNEL, long-term	inhalation	local	0,6 mg/m ³
Worker DNEL, acute	inhalation	local	6,0 mg/m ³
Worker DNEL, acute	dermal	local	2,8 mg/person/day
Worker DNEL, long-term	dermal	local	0,28 mg/person/day
Worker DNEL, acute	dermal	systemic	mg/kg bw/day
1477-55-0	m-Phenylenebis(methylamine)		
Worker DNEL, long-term	inhalation	systemic	1,2 mg/m ³
Worker DNEL, long-term	inhalation	local	0,2 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,33 mg/kg bw/day

PNEC values

CAS No	Substance	
Environmental compartment	Value	
1477-55-0	m-Phenylenebis(methylamine)	
Freshwater	0,094 mg/l	
Marine water	0,009 mg/l	
Freshwater sediment	0,43 mg/kg	
Marine sediment	0,043 mg/kg	
Micro-organisms in sewage treatment plants (STP)	10 mg/l	
Soil	0,045 mg/kg	
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol	
Freshwater	0,084 mg/l	
Marine water	0,0084 mg/l	
Micro-organisms in sewage treatment plants (STP)	0,2 mg/l	

Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Individual protection measures, such as personal protective equipment



Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. B

Revision date: 13.12.2022

Page 8 of 17

Eye/face protection

Wear eye/face protection. Wear safety glasses.

Hand protection

Recommended material: NBR (Nitrile rubber)

Breakthrough time: > 480 min

Thickness of the glove material: 0,7 mm

DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	solid (pasty)
Colour:	black / red
Odour:	characteristic
Odour threshold:	No data available

Changes in the physical state

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flash point:	not applicable

Flammability

Solid/liquid:	not determined
Gas:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined

Self-ignition temperature

Solid:	not determined
Gas:	not applicable
Decomposition temperature:	not determined
pH-Value:	not applicable

Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
-------------------	--

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	1,07 g/cm ³
Relative vapour density:	not determined



Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. B

Revision date: 13.12.2022

Page 9 of 17

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties

Not oxidising.

Other safety characteristics

Solid content:

not determined

Evaporation rate:

not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

see section 10.3

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent, strong

10.4. Conditions to avoid

see section 7.2

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Harmful if swallowed.

ATEmix calculated

ATE (oral) 751,3 mg/kg; ATE (dermal) 7761,8 mg/kg; ATE (inhalation vapour) 5,73 mg/l; ATE (inhalation dust/mist) 0,621 mg/l

Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. B

Revision date: 13.12.2022

Page 10 of 17

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine				
	oral	ATE 1030 mg/kg			
1477-55-0	m-Phenylenebis(methylamine)				
	oral	LD50 930 mg/kg	Rat		
	dermal	LD50 2000 mg/kg	Rabbit		
	inhalation (1 h) vapour	LC50 3,89 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol				
	oral	LD50 2169 mg/kg	Rat		
	dermal	LD50 1280 mg/kg	Rat		
100-51-6	Benzyl alcohol				
	oral	LD50 1230 mg/kg	Rat		
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
111-40-0	Diethylenetriamine				
	oral	LD50 1080 mg/kg	Rat		
	dermal	LD50 1054 mg/kg	Rabbit		
	inhalation vapour	ATE 0,5 mg/l			
	inhalation dust/mist	ATE 0,05 mg/l			
108-95-2	Phenol				
	oral	LD50 650 mg/kg	Rat		OECD 401
	dermal	LD50 630 mg/kg	Rabbit		
	inhalation vapour	ATE 3 mg/l			
	inhalation dust/mist	LC50 0,9 mg/l	8 h Rat		
80-05-7	Bisphenol A				
	oral	LD50 3250 mg/kg	Rat		
	dermal	LD50 3000 mg/kg	Rabbit		

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (3-aminomethyl-3,5,5-trimethylcyclohexylamine; Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine); m-Phenylenebis(methylamine); Formaldehyde, oligomeric reaction products with 4,4'-isopropylidenediphenol and diethylenetriamine; Diethylenetriamine; Bisphenol A)

Carcinogenic/mutagenic/toxic effects for reproduction



Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. B

Revision date: 13.12.2022

Page 11 of 17

Suspected of causing genetic defects. (Phenol)

May damage fertility. (Bisphenol A)

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

This mixture is placed on the market in a form in which aerosol formation cannot occur during intended use and may only be used for applications in which aerosol formation is excluded. Workplace measurements to determine the exposure of users towards contained hazardous substances were carried out. Test reports show no need for the classification of the product as toxic by inhalation. The test reports are available. According to Article 6 of Regulation EC No. 1272/2008, classification and labeling as inhalation toxic is therefore not required.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. B

Revision date: 13.12.2022

Page 12 of 17

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1477-55-0	m-Phenylenebis(methylamine)					
	Acute fish toxicity	LC50 mg/l	87,6	96 h	Oryzias latipes (Ricefish)	OECD 203
	Acute algae toxicity	ErC50 mg/l	32,1	72 h	Selenastrum capricornutum	OECD 201
	Acute crustacea toxicity	EC50 mg/l	15,2	48 h	Daphnia magna (Big water flea)	OECD 202
	Crustacea toxicity	NOEC	4,7 mg/l	21 d	Daphnia magna (Big water flea)	OECD 211
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol					
	Acute fish toxicity	LC50	175 mg/l	96 h	Cyprinus carpio (Common Carp)	
	Acute algae toxicity	ErC50	84 mg/l	72 h	Desmodesmus subspicatus	OECD 201
	Algae toxicity	NOEC	6,25 mg/l	3 d		
111-40-0	Diethylenetriamine					
	Acute fish toxicity	LC50	430 mg/l	96 h	Leuciscus idus	
	Acute algae toxicity	ErC50 mg/l	1164	72 h	Selenastrum capricornutum	
	Acute crustacea toxicity	EC50 mg/l	53,5	48 h	Daphnia magna	
108-95-2	Phenol					
	Acute fish toxicity	LC50	8,9 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 mg/l	61,1	96 h		
	Acute crustacea toxicity	EC50	3,1 mg/l	48 h	Daphnia magna (Big water flea)	
	Crustacea toxicity	NOEC	0,16 mg/l	16 d	Daphnia magna (Big water flea)	
80-05-7	Bisphenol A					
	Acute fish toxicity	LC50	< 1 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute crustacea toxicity	EC50	< 1 mg/l	48 h	Daphnia magna (Big water flea)	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
80-05-7	Bisphenol A			
	OECD 301F	74,7 - 81,4	28	

12.3. Bioaccumulative potential

The product has not been tested.



Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. B

Revision date: 13.12.2022

Page 13 of 17

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	1,9
1477-55-0	m-Phenylenebis(methylamine)	0,18
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol	0,219
100-51-6	Benzyl alcohol	1,05
111-40-0	Diethylenetriamine	-5,58
108-95-2	Phenol	1,5
80-05-7	Bisphenol A	3,4

BCF

CAS No	Chemical name	BCF	Species	Source
1477-55-0	m-Phenylenebis(methylamine)	2,69		
108-95-2	Phenol	17,5		
80-05-7	Bisphenol A	73		

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. B

Revision date: 13.12.2022

Page 14 of 17

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-Phenylenebis(methylamine))
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8



Classification code: C8
 Special Provisions: 274
 Limited quantity: 1 kg
 Excepted quantity: E2
 Transport category: 2
 Hazard No: 80
 Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-Phenylenebis(methylamine))
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8



Classification code: C8
 Special Provisions: 274
 Limited quantity: 1 kg
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-Phenylenebis(methylamine))
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8



Special Provisions: 274
 Limited quantity: 1 kg
 Excepted quantity: E2
 EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-Phenylenebis(methylamine))

Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. B

Revision date: 13.12.2022

Page 15 of 17

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

Hazard label:

8



Special Provisions:

A3 A803

Limited quantity Passenger:

5 kg

Passenger LQ:

Y844

Excepted quantity:

E2

IATA-packing instructions - Passenger:

859

IATA-max. quantity - Passenger:

15 kg

IATA-packing instructions - Cargo:

863

IATA-max. quantity - Cargo:

50 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes


14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):

Bisphenol A

Restrictions on use (REACH, annex XVII):

Entry 66, Entry 75

 Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)
 (SEVESO III):

Additional information

VOC content: 28,7 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. B

Revision date: 13.12.2022

Page 16 of 17

SECTION 16: Other information

Abbreviations and acronyms

ADN: Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation
(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
CAS: Chemical Abstracts Service
CLP: Classification, Labeling and Packaging
DMEL: Derived Minimal Effect level
DNEL: Derived No Effect Level
EC50: Effective concentration, 50%
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)
IMDG: International Maritime Dangerous Goods Code
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
NOEC: No Observed Effect Concentration
OECD: Organisation for Economic Co-operation and Development
PBT: persistent, bioaccumulative and toxic
vPvB: very persistent and very bioaccumulative
PNEC: Predicted No Effect Concentration
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail)
VOC: Volatile organic compound
Acute Tox. 2: Acute toxicity, Category 2
Acute Tox. 3: Acute toxicity, Category 3
Acute Tox. 4: Acute toxicity, Category 4
Aquatic Chronic 3: Long-term aquatic hazard, Category 3
Eye Dam. 1: Serious eye damage/eye irritation, Category 1
Eye Irrit. 2: Serious eye damage/eye irritation, Category 2
Repr. 1B: Reproductive toxicity, Category 1B
Skin Sens. 1: Skin sensitization, Category 1
Skin Sens. 1B: Skin sensitization, Category 1B
STOT RE 2: Specific target organ toxicity (repeated exposure), Category 2
STOT SE 3: Specific target organ toxicity (single exposure), Category 3

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Muta. 2; H341	Calculation method
Repr. 1A; H360F	
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.



Safety Data Sheet

according to UK REACH Regulation

ATA 2004C, Comp. B

Revision date: 13.12.2022

Page 17 of 17

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H360F	May damage fertility.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)